

Professional Series 17" Prompter (PSP17)

Key Features and Selling Points



- High bright prompter for large studio – supplied with same accessories as Master Series
- Monitor has scan reverse, external PSU, composite and VGA inputs, and 1-year warranty
- Lightweight and collapsible wide-angle hood for all lens types at no extra cost
- Fully adjustable hood and mounting system – shoot directly through the centre of the glass without raising the camera up and away from the fluid head, creating a pendulum effect and reducing control
- Pro Plate slides back and forth to accommodate any size camera and lens
- Prompter is counter balanced by sliding the Pro Plate back and using the weight of the camera and/ or adding slide-on weights to the back of the Pro Plate

Package Options and Technical Specifications

- **Standard Package (PSP17LWAPP):** PSP17 Monitor, Large Wide Angle hood, bracket and glass, Pro Plate, 25m composite cable (software and hand controls not included)
- **Full Assembly Weight:** 11.4kgs
- **Glass:** 70:30 transmission with internal anti-reflective coating
- **Alternative Mounting Options:** Long (12") or short (7.5") rods for pedestals
- **Optional Extras:** Cuelight Kit, Talent Feedback Monitor 17" (TFM17), Counter-balance weights
- **Software Options:** QStart, QPro, QMaster or any other prompting software

Monitor Size	17" (432mm)
Reading Range	6m (20ft)
Brightness	420 Nits
Resolution	720 x 400
Contrast Ratio	500 : 1
Input Signal	Composite, VGA
Composite Standard	NTSC, PAL, SECAM
Power Input	12 V DC (2.1 mm jack)
Power Consumption	36W

Professional prompting for small to medium-sized broadcasters and intermediate productions

Professional Series monitor sizes: 5", 8", 10", 12", 17"

Professional Series 12" Prompter (PSP12)

Key Features and Selling Points



- High bright mid-size prompter for studio use – supplied with same accessories as Master Series
- Monitor has scan reverse, external PSU, composite and VGA inputs, and 1-year warranty
- Lightweight and collapsible wide-angle hood for all lens types at no extra cost
- Fully adjustable hood and mounting system – shoot directly through the centre of the glass without raising the camera up and away from the fluid head, creating a pendulum effect and reducing control
- Gold Plate slides back and forth to accommodate any DV or ENG camera and lens
- Prompter is counter balanced by sliding the camera plate back and using the weight of the camera and/ or adding slide-on weights to the back of the Gold Plate

Package Options and Technical Specifications

- **Standard Package (PSP12MWAGP):** PSP12 Monitor, Medium Wide Angle hood, bracket and glass, Gold Plate, 25m composite cable (software and hand controls not included)
- **Full Assembly Weight:** 7.6kgs
- **Glass:** 70:30 transmission with internal anti-reflective coating
- **Alternative Mounting Options:** Long (12") or short (7.5") rods for pedestals, additional camera carriage
- **Optional Extras:** Cuelight, Talent Feedback Monitor 9" (TFM09), Counter-balance weights, Additional Camera Carriage, Steady Bar Kit
- **Software Options:** QStart, QPro, QMaster or any other prompting software

Monitor Size	12.1" (307mm)
Reading Range	4.5m (15ft)
Brightness	400 Nits
Resolution	720 x 400
Contrast Ratio	500 : 1
Input Signal	Composite, VGA
Composite Standard	NTSC, PAL, SECAM
Power Input	12 V DC (2.1 mm jack)
Power Consumption	25W

Professional prompting for small to medium-sized broadcasters and intermediate productions

Professional Series monitor sizes: 5", 8", 10", 12", 17"

Professional Series 10" Prompter (PSP10)

Key Features and Selling Points



- High bright mid-size prompter for studio use – supplied with same accessories as Master Series
- Monitor has scan reverse, external PSU, composite and VGA inputs, and 1-year warranty
- Lightweight and collapsible wide-angle hood for all lens types at no extra cost
- Fully adjustable hood and mounting system – shoot directly through the centre of the glass without raising the camera up and away from the fluid head, creating a pendulum effect and reducing control
- Gold Plate slides back and forth to accommodate any DV or ENG camera and lens
- Prompter is counter balanced by sliding the camera plate back and using the weight of the camera and/ or adding slide-on weights to the back of the Gold Plate

Package Options and Technical Specifications

- **Standard Package (PSP10SWAGP):** PSP10 Monitor, Small Wide Angle hood, bracket and glass, Gold Plate, 25m composite cable (software and hand controls not included)
- **Full Assembly Weight:** 4.0kgs
- **Glass:** 70:30 transmission with internal anti-reflective coating
- **Alternative Mounting Options:** Additional camera carriage
- **Optional Extras:** Mini Cuelight, Additional Camera Carriage, Medium Wide Angle hood
- **Software Options:** QStart, QPro, QMaster or any other prompting software

Monitor Size	10.4" (264mm)
Reading Range	4m (13ft)
Brightness	400 Nits
Resolution	720 x 400
Contrast Ratio	500 : 1
Input Signal	Composite, VGA
Composite Standard	NTSC, PAL, SECAM
Power Input	12 V DC (2.1 mm jack)
Power Consumption	20W

Professional prompting for small to medium-sized broadcasters and intermediate productions

Professional Series monitor sizes: 5", 8", 10", 12", 17"

Professional Series 8" Prompter (PSP08)

Key Features and Selling Points



- High bright portable prompter for studio use – supplied with same accessories as Master Series
- Monitor has scan reverse, external PSU, composite input, and 1-year warranty
- Lightweight and collapsible wide-angle hood for all lens types at no extra cost
- Fully adjustable hood and mounting system – shoot directly through the centre of the glass without raising the camera up and away from the fluid head, creating a pendulum effect and reducing control
- Gold Plate slides back and forth to accommodate any DV or ENG camera and lens
- Prompter is counter balanced by sliding the camera plate back and using the weight of the camera and/ or adding slide-on weights to the back of the Gold Plate

Package Options and Technical Specifications

- **Standard Package (PSP08SWAGP):** PSP08 Monitor, Small Wide Angle hood, bracket and glass, Gold Plate, 25m composite cable (software and hand controls not included)
- **Full Assembly Weight:** 3.1kgs
- **Glass:** 70:30 transmission with internal anti-reflective coating
- **Alternative Mounting Options:** Additional camera carriage
- **Optional Extras:** Mini Cuelight, Additional Camera Carriage
- **Software Options:** QStart, QPro, QMaster or any other prompting software

Monitor Size	8" (203mm)
Reading Range	3m (10ft)
Brightness	500 Nits
Resolution	640 x 480
Contrast Ratio	500 : 1
Input Signal	Composite, RGB phono
Composite Standard	NTSC, PAL, SECAM
Power Input	12 V DC (2.1 mm jack)
Power Consumption	14.4W

Professional prompting for small to medium-sized broadcasters and intermediate productions

Professional Series monitor sizes: 5", 8", 10", 12", 17"

Professional Series 5" Prompter (PSP05)

Key Features and Selling Points



- The smallest high bright prompter in the world – supplied with same accessories as Master Series
- Monitor has scan reverse, external PSU, composite input, and 1-year warranty
- Lightweight and collapsible wide-angle hood for all lens types at no extra cost
- Fully adjustable hood and mounting system – shoot directly through the centre of the glass without raising the camera up and away from the fluid head, creating a pendulum effect and reducing control
- Gold Plate slides back and forth to accommodate any DV or ENG camera and lens
- Prompter is counter balanced by sliding the camera plate back and using the weight of the camera and/ or adding slide-on weights to the back of the Gold Plate

Package Options and Technical Specifications

- **Standard Package (PSP05SWAGP):** PSP05 Monitor, Small Wide Angle hood, bracket and glass, Gold Plate, 25m composite cable (software and hand controls not included)
- **Full Assembly Weight:** 2.7kgs
- **Glass:** 70:30 transmission with internal anti-reflective coating
- **Alternative Mounting Options:** Additional camera carriage
- **Optional Extras:** Mini Cuelight Kit, Additional Camera Carriage
- **Software Options:** QStart, QPro, QMaster or any other prompting software

Monitor Size	5.6" (145mm)
Reading Range	2 m (7 ft)
Brightness	300 Nits
Resolution	960 x 234
Contrast Ratio	250 : 1
Input Signal	Composite, RCA
Composite Standard	NTSC, PAL
Power Input	12 V DC (2.1 mm jack)
Power Consumption	10W

Professional prompting for small to medium-sized broadcasters and intermediate productions

Professional Series monitor sizes: 5", 8", 10", 12", 17"